


CIRCUIT DIAGRAM



PCB LAYOUT

SPECIFICATIONS

Rating	DC 12V 50mA.		
Contact Resistance	100 m $\Omega$ Max.		
Operating Force	2	180 $\pm$ 50gf	3 260 $\pm$ 50gf
Operating Life (cycles)	100,000		

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
8	HOUSING	1	PA66	
7	TAPE	1	SILICON RUBBER	
6	FILM	1	GATHERS THE IMIDE	
5	PLUG	1	PA66	
4	CONTACT	1	SUS	Ag plated
3	FRAME	1	PPS	Ag plated
2	PLATE LAYER	1	CYANIDE	
1	TERMINAL	1	BRASS	Ag plated
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

東莞市高迪電子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5  $\pm$  0.2  
 Above 5 ~ 15  $\pm$  0.3  
 Above 15 ~ 30  $\pm$  0.4  
 Above 30 ~ 50  $\pm$  0.5  
 Angle  $\pm$  0.3

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SIZE
Jack Lu	08/28/18		SWITCH	A4
CHECKED BY:	DATE	FINISH	MODLE	VER
Jacky Chen	08/28/18		防水 TACT SWITCH	R
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	08/28/18	1 : 1	TS-A62W-x-S138	
		SHEET NO.	PART NO.	
		1 of 1	TS-A62W-x-S138	

ITEM NO.	DESCRIPTION	DRAWN	DATE