



## 两档滑动开关

1. 滑动开关型号 SLIDE SWITCH MODEL: SFD-1-22AAD
2. 焊线端子 SOLDER CONNECTOR TYPE; 双刀双掷 DOUBLE POLE DOUBLE THROW
3. 额定值 RATING: ▲ 16(4)A 125/250VAC  $\mu$ T105  
10(2)A 125/250VAC  $\mu$ T105

▲ 16A 125/250VAC  $\mu$ T105  
10(2)A 125/250VAC  $\mu$ T85

4. 接触电阻 CONTACT RESISTANCE: <50m $\Omega$  (INITIAL)
5. 绝缘电阻 INSULATION RESISTANCE:  $\geq$ 100M $\Omega$ (DC500V/1MIN)
6. 介电强度 DIELECTRIC STRENGTH: 1500V /5mA /1MIN
7. 机械寿命 MECHANICAL LIFE: >50000 CYCLES
8. 电气寿命 ELECTRICAL LIFE: >10000 CYCLES
9. 端子手工焊接条件 SOLDER ABILITY OF TERMINAL: MAX260°C. 3S
10. 操作力 OPERATION FORCE: 550 $\pm$ 150gf
11. 所有部件均使用环保材料 ALL MATERIALS ARE RoHS COMPLIANT

NO.	PARTS	MATERIALS	QTY	FINISH
5	CONTACT CLIP	PBS STRIP	1	Ag PLATED
4	TERMINAL	BRASS	3	Ag PLATED
3	BASE	PHENOLIC RESIN	1	NATURAL
2	FRAME	STEEL STRIP	1	Ni PLATED
1	KNOB	POM	1	BLACK



东莞市高迪电子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:  
Up to 5  $\pm$ 0.2  
Above 5 ~ 15  $\pm$ 0.3  
Above 15 ~ 30  $\pm$ 0.4  
Above 30 ~ 50  $\pm$ 0.5  
Angle  $\pm$ 0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY: DATE  
Ming Ming Zou 11/19/14

CHECKED BY: DATE  
Ning Ning Su 11/19/14

APPROVED BY: DATE  
Jia Xiang 11/19/14

MAT'L	TITLE	SWITCH
FINISH	MODLE	SLIDE SWITCH
SCALE	DWG NO.	GD-SFD-1-22AAD
SHEET NO.	PART NO.	

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增SPEC	Jack	111914
1	新增尺寸	Jack	061614

SIZE  
A4  
VER  
R2